



1	单位	mm	UNSPECIFIED TOLERANCE:(GB/T1804-2000) <table border="1"> <thead> <tr> <th>SIZE</th> <th>TOL</th> <th>ANG.TOLERANCE</th> </tr> </thead> <tbody> <tr> <td>等级</td> <td>精度 (F)</td> <td>等级</td> <td>最粗 (V)</td> </tr> <tr> <td>0~6</td> <td>±0.05</td> <td>0~10</td> <td>±3'</td> </tr> <tr> <td>&gt;6~30</td> <td>±0.1</td> <td>&gt;10~50</td> <td>±2'</td> </tr> <tr> <td>&gt;30~120</td> <td>±0.15</td> <td>&gt;50~120</td> <td>±1'</td> </tr> <tr> <td>&gt;120~400</td> <td>±0.2</td> <td>&gt;120~400</td> <td>±30'</td> </tr> <tr> <td>&gt;400~1000</td> <td>±0.3</td> <td>&gt;400</td> <td>±20'</td> </tr> <tr> <td>&gt;1000~2000</td> <td>±0.5</td> <td></td> <td></td> </tr> <tr> <td>&gt;2000</td> <td>--</td> <td></td> <td></td> </tr> </tbody> </table>	SIZE	TOL	ANG.TOLERANCE	等级	精度 (F)	等级	最粗 (V)	0~6	±0.05	0~10	±3'	>6~30	±0.1	>10~50	±2'	>30~120	±0.15	>50~120	±1'	>120~400	±0.2	>120~400	±30'	>400~1000	±0.3	>400	±20'	>1000~2000	±0.5			>2000	--		
	SIZE	TOL		ANG.TOLERANCE																																		
等级	精度 (F)	等级	最粗 (V)																																			
0~6	±0.05	0~10	±3'																																			
>6~30	±0.1	>10~50	±2'																																			
>30~120	±0.15	>50~120	±1'																																			
>120~400	±0.2	>120~400	±30'																																			
>400~1000	±0.3	>400	±20'																																			
>1000~2000	±0.5																																					
>2000	--																																					
比例																																						
投影																																						
修订	修订内容	日期																																				

Zhejiang Yixiong M&E  
Manufacturer Co., LTD.

型号	VJ52-16	共 页	第 页
客户		批 准	
图号		核 对	
版本		设 计	侯长勇 18.06.12